

NEW

ABORA



S1P

S1P EN ISO 20345 : 2022 S1P SR FO CI HI

2022 STANDARD VERSION



■ 9822 BLUE | 36 ► 47

PRODUCT CHARACTERISTICS



Hydrocarbon resistance



Insulated sole (cold)



Insulated sole (heat)



ESD

PARADE TECHNOLOGIES



Supports the arch of the foot

• PERFECT FOR HOT WORK ENVIRONMENT WITH ITS BREATHABLE MICROFIBRE UPPER

COMPOSITION

Upper	Microfibre
Lining	3D Mesh
Toe	Steel
Insole	Mesh over PU foam. Removable
Anti-puncture sole	Metallic
Sole	Two-density polyurethane
Weight size 42*	610g *Weight per shoe

**

Size coefficient 42	front		heel	
	Standard	Parade	Standard	Parade
Ceramic floor / Nals (soap solution)	0,36	0,42	0,31	0,22
SR Ceramic floor / Glycerine	0,22	0,33	0,19	0,20

SAFETY TABLE

	Toe protection (Safety toe cap)
	Slip-resistance ** Ceramic flooring + detergent
	Energy-absorbing heel
	Anti-static
	Puncture-resistance Metallic insert Small spike test (4,5 mm)
	Slip-resistance ** (ceramic floor + detergent)
	Hydrocarbon resistance
	Sole insulation (cold)
	Sole insulation (heat)