

ASTON

S3

EN ISO 20345 : 2022+A1 : 2024 S3
SR FO CI HI ESD
ASTM F2413-24

2022 STANDARD VERSION



■ 1804 BLACK | 36 ► 47



■ 1803 BROWN | 36 ► 47

COMPOSITION

Upper	Leather
Lining	3D mesh
Toe	Steel
Insole	Mesh over PU foam. Removable
Anti-puncture sole	Metallic
Sole	Dual-density polyurethane
Weight size 42*	725 g *Weight per shoe

**

Size 42	front		heel	
	Standard	Parade	Standard	Parade
Ceramic floor / Nals (soap solution)	0,36	0.42	0,31	0.33
SR Ceramic floor + glycerine	0,22	0.22	0,19	0.20

PRODUCT FEATURES



Sole insulation (cold)



Sole insulation (heat)



ESD

EXTRAS PARADE TECHNOLOGY



Arch support

- EASY TO PUT ON AND TAKE OFF
- EASY-TO-CLEAN LEATHER

SAFETY TABLE



Toe protection
(Safety toe cap)



Slip-resistance **
Ceramic flooring + detergent



Energy-absorbing heel



Anti-static



Puncture-resistance
Metallic insert
Wide spike test (4.5 mm)



Water-repellent upper



Slip-resistance **
(ceramic flooring + oil)



Hydrocarbon resistance



Sole insulation (cold)



Sole insulation (heat)



Electrostatic dissipation