

NEW

RAKING



S3 EN ISO 20345: 2022 S3 SR FO CI HI

STANDARD VERSION 2022



8844 BLACK | 35 ▶ 48

PRODUCT CHARACTERISTICS



Insulated sole (cold)



Insulated sole (heat)



ESD

PARADE

TECHNOLOGIES



Supports the arch of the foot



New DRS version



Extra-flexible sole

COMPOSITION

Upper	Microfibre + PU
Front reinforcement	Injected PU
Lining	3D mesh
Toe cap	Steel
Insole	Mesh over PU foam. Removable.
Anti-puncture sole	Stainless steel
Sole	Two-density polyurethane
Weight size 42*	630 g * Weight per shoe

**	Coefficient obtained size 42	Front		Heel	
		Standard	Parade	Standard	Parade
	Ceramic floor / Nals (soap solution)	0,36	0,36	0,31	0,34
	SR Ceramic floor + Glycerine	0,22	0,23	0,19	0,26

SAFETY TABLE



Toe protection (safety toe cap)



Slip resistance **
Ceramic floors + detergent



Energy-absorbing heel



Anti-static



Puncture-resistance
Metallic insert
Wide point test (4.5 mm)



Slip resistance **
(ceramic floor + oil)



Water-repellent upper



Hydrocarbon-resistant



Sole insulation (cold)



Sole insulation (heat)



Electrostatic dissipation