

ROOVER



S3S EN ISO 20345: 2022 S3S SR FO CI HI

STANDARD
VERSION 2022



1844 BLACK | 35 ▶ 48

PRODUCT CHARACTERISTICS



Leather upper



Insulated sole (cold)



Insulated sole (heat)



ESD

PARADE TECHNOLOGIES



Supports the arch of the foot



New DRS version



Extra-flexible sole

• REFLECTIVE MATERIAL ON THE SHOE

COMPOSITION

Upper	Leather
Lining	3D mesh
Toe	Composite
Insole	Mesh over PU foam. Removable.
Anti-puncture sole	Fabric
Sole	Two-density polyurethane
Weight size 42*	610 g *Weight per shoe

SAFETY TABLE



Toe protection (safety toe cap)



Slip resistance **
Ceramic floors + detergent



Energy-absorbing heel



Anti-static



Puncture-resistance
Non-metallic insert
SP = small point 3 mm



Slip resistance **
(ceramic floor + oil)



Water-repellent upper



Hydrocarbon-resistant



Sole insulation (cold)



Sole insulation (heat)



Electrostatic dissipation

**

Coefficient obtained size	Front		Heel	
	Standard	Parade	Standard	Parade
Ceramic floor / Nals (soap solution)	0.36	0.36	0.31	0.32
SR Ceramic floor + Glycerine	0.22	0.27	0.19	0.20